

Compact pilot light 22 mm plastic round integrated LED 24V AC/DC red



product brand name	SIRIUS
product category	Commanding and signaling devices
product designation	Indicator light
design of the product	Compact unit
product type designation	3SB6
product line	Plastic, black, 22 mm
product component front ring	No
product component light source	No
Substance Prohibittance (Date)	03/01/2017
Weight	20.2 g
ambient temperature	
• during operation	-25 ... +70 °C
• during storage	-40 ... +80 °C
fastening method	nut
mounting diameter	22 mm
mounting height	38 mm
installation width	20 mm

Approvals Certificates

General Product Approval	other	Environment
--------------------------	-------	-------------



[Confirmation](#)

[Environmental Confirmations](#)

Further information

Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3SB6213-6AA20-1AA0>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3SB6213-6AA20-1AA0>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3SB6213-6AA20-1AA0>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3SB6213-6AA20-1AA0&lang=en

last modified:

12/21/2020

Compact pilot light 22 mm plastic round integrated LED 24V AC/DC yellow



Figure similar

product brand name	SIRIUS
product category	Commanding and signaling devices
product designation	Indicator light
design of the product	Compact unit
product type designation	3SB6
product line	Plastic, black, 22 mm
product component front ring	No
product component light source	No
Substance Prohibitance (Date)	03/01/2017
Weight	20.2 g
ambient temperature	
• during operation	-25 ... +70 °C
• during storage	-40 ... +80 °C
fastening method	nut
mounting diameter	22 mm
mounting height	38 mm
installation width	20 mm

Approvals Certificates

General Product Approval



[Confirmation](#)



other	Environment
-------	-------------

[Miscellaneous](#)

[Confirmation](#)

[Environmental Confirmations](#)

Further information

Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3SB6213-6AA30-1AA0>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3SB6213-6AA30-1AA0>


Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3SB6213-6AA30-1AA0>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3SB6213-6AA30-1AA0&lang=en

last modified:

12/21/2020 

Compact pilot light 22 mm plastic round integrated LED 24V AC/DC green



Figure similar

product brand name	SIRIUS
product category	Commanding and signaling devices
product designation	Indicator light
design of the product	Compact unit
product type designation	3SB6
product line	Plastic, black, 22 mm
product component front ring	No
product component light source	No
Substance Prohibitance (Date)	03/01/2017
Weight	20.2 g
ambient temperature	
• during operation	-25 ... +70 °C
• during storage	-40 ... +80 °C
fastening method	nut
mounting diameter	22 mm
mounting height	38 mm
installation width	20 mm

Approvals Certificates

General Product Approval	other	Environment
--------------------------	-------	-------------



[Confirmation](#)

[Environmental Confirmations](#)

Further information

Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3SB6213-6AA40-1AA0>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3SB6213-6AA40-1AA0>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3SB6213-6AA40-1AA0>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3SB6213-6AA40-1AA0&lang=en

last modified:

12/21/2020

Compact pilot light 22 mm plastic round integrated LED 220V AC red



product brand name	SIRIUS
product category	Commanding and signaling devices
product designation	Indicator light
design of the product	Compact unit
product type designation	3SB6
product line	Plastic, black, 22 mm
product component front ring	No
product component light source	No
Substance Prohibittance (Date)	03/01/2017
Weight	20.2 g
ambient temperature	
• during operation	-25 ... +70 °C
• during storage	-40 ... +80 °C
fastening method	nut
mounting diameter	22 mm
mounting height	38 mm
installation width	20 mm

Approvals Certificates

General Product Approval	other	Environment
--------------------------	-------	-------------



EG-Konf.



[Confirmation](#)

[Environmental Confirmations](#)

Further information

Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3SB6216-6AA20-1AA0>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3SB6216-6AA20-1AA0>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3SB6216-6AA20-1AA0>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3SB6216-6AA20-1AA0&lang=en

last modified:

12/21/2020

Compact pilot light 22 mm plastic round integrated LED 220V AC yellow



Figure similar

product brand name	SIRIUS
product category	Commanding and signaling devices
product designation	Indicator light
design of the product	Compact unit
product type designation	3SB6
product line	Plastic, black, 22 mm
product component front ring	No
product component light source	No
Substance Prohibitance (Date)	03/01/2017
Weight	20.2 g
ambient temperature	
• during operation	-25 ... +70 °C
• during storage	-40 ... +80 °C
fastening method	nut
mounting diameter	22 mm
mounting height	38 mm
installation width	20 mm

Approvals Certificates

General Product Approval	other	Environment
--------------------------	-------	-------------



EG-Konf.



[Confirmation](#)

[Environmental Confirmations](#)

Further information

Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3SB6216-6AA30-1AA0>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3SB6216-6AA30-1AA0>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3SB6216-6AA30-1AA0>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3SB6216-6AA30-1AA0&lang=en

last modified:

12/21/2020

Compact pilot light 22 mm plastic round integrated LED 220V AC green



Figure similar

product brand name	SIRIUS
product category	Commanding and signaling devices
product designation	Indicator light
design of the product	Compact unit
product type designation	3SB6
product line	Plastic, black, 22 mm
product component front ring	No
product component light source	No
Substance Prohibitance (Date)	03/01/2017
Weight	20.2 g
ambient temperature	
• during operation	-25 ... +70 °C
• during storage	-40 ... +80 °C
fastening method	nut
mounting diameter	22 mm
mounting height	38 mm
installation width	20 mm

Approvals Certificates

General Product Approval	other	Environment
--------------------------	-------	-------------



[Confirmation](#)

[Environmental Confirmations](#)

Further information

Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3SB6216-6AA40-1AA0>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3SB6216-6AA40-1AA0>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3SB6216-6AA40-1AA0>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3SB6216-6AA40-1AA0&lang=en

last modified:

12/21/2020

Compact pilot light 22 mm plastic round integrated LED 220V AC blue



Figure similar

product brand name	SIRIUS
product category	Commanding and signaling devices
product designation	Indicator light
design of the product	Compact unit
product type designation	3SB6
product line	Plastic, black, 22 mm
product component front ring	No
product component light source	No
Substance Prohibitance (Date)	03/01/2017
Weight	20.2 g
ambient temperature	
• during operation	-25 ... +70 °C
• during storage	-40 ... +80 °C
fastening method	nut
mounting diameter	22 mm
mounting height	38 mm
installation width	20 mm

Approvals Certificates

General Product Approval	other	Environment
--------------------------	-------	-------------



[Confirmation](#)

[Environmental Confirmations](#)

Further information

Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3SB6216-6AA50-1AA0>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3SB6216-6AA50-1AA0>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3SB6216-6AA50-1AA0>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3SB6216-6AA50-1AA0&lang=en

last modified:

12/21/2020

Compact pilot light 22 mm plastic round integrated LED 220V AC white



Figure similar

product brand name	SIRIUS
product category	Commanding and signaling devices
product designation	Indicator light
design of the product	Compact unit
product type designation	3SB6
product line	Plastic, black, 22 mm
product component front ring	No
product component light source	No
Substance Prohibitance (Date)	03/01/2017
Weight	20.2 g
ambient temperature	
• during operation	-25 ... +70 °C
• during storage	-40 ... +80 °C
fastening method	nut
mounting diameter	22 mm
mounting height	38 mm
installation width	20 mm

Approvals Certificates

General Product Approval	other	Environment
--------------------------	-------	-------------



[Confirmation](#)

[Environmental Confirmations](#)

Further information

Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3SB6216-6AA60-1AA0>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3SB6216-6AA60-1AA0>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3SB6216-6AA60-1AA0>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3SB6216-6AA60-1AA0&lang=en

last modified:

12/21/2020

