



SIMATIC S7-1500, TM PTO 4 interface module for stepper drives 4 channels pulse train output PTO: 24 V, RS-422, 5 V, 2 DI, 1 DQ 24 V DC per channel

General information	
Product type designation	TM PTO 4
Number of channels	4; Axes
Product function	
<ul style="list-style-type: none"> I&M data Isochronous mode 	Yes; I&M0 to I&M3 Yes
Engineering with	
<ul style="list-style-type: none"> STEP 7 TIA Portal configurable/integrated from version STEP 7 configurable/integrated from version PROFINET from GSD version/GSD revision 	STEP 7 V19 or higher V5.5 SP3 with GSD file / - GSDML V2.43
Installation type/mounting	
Rail mounting	Yes; S7-1500 mounting rail
Supply voltage	
Load voltage L+	
<ul style="list-style-type: none"> Rated value (DC) permissible range, lower limit (DC) permissible range, upper limit (DC) Reverse polarity protection 	24 V 19.2 V 28.8 V Yes
Input current	
Current consumption, max.	70 mA; without load
Power	
Power consumption from the backplane bus	1.3 W
Power loss	
Power loss, typ.	4 W
Address area	
Address space per module	
<ul style="list-style-type: none"> Inputs Outputs 	72 byte; 18 per channel 40 byte; 10 per channel
Digital inputs	
Number of digital inputs	12; 3 per channel, of which 1 DIQ
Digital inputs, parameterizable	Yes
Input characteristic curve in accordance with IEC 61131, type 3	Yes
Digital input functions, parameterizable	
<ul style="list-style-type: none"> Synchronization Probe Drive ready 	Yes Yes Yes
Input voltage	
<ul style="list-style-type: none"> Type of input voltage Rated value (DC) for signal "0" 	DC 24 V -5 ... +5 V

<ul style="list-style-type: none"> • for signal "1" • permissible voltage at input, min. • permissible voltage at input, max. 	+11 to +30V -5 V 30 V
Input current	
<ul style="list-style-type: none"> • for signal "1", typ. 	2.5 mA
Input delay (for rated value of input voltage)	
for standard inputs	
— parameterizable	Yes; none / 0.05 / 0.1 / 0.4 / 0.8 / 1.6 / 3.2 / 12.8 / 20 ms
for technological functions	
— parameterizable	Yes
Cable length	
<ul style="list-style-type: none"> • shielded, max. • unshielded, max. 	1 000 m 600 m
Digital outputs	
Number of digital outputs	12; 3 per channel, of which 1 DIQ
Current-sinking	Yes; For DQn.0 and DQn.1 push-pull outputs
Current-sourcing	Yes
Digital outputs, parameterizable	Yes
Short-circuit protection	Yes; electronic/thermal
<ul style="list-style-type: none"> • Response threshold, typ. 	0.2 A for DQn.0 and DQn.1, 0.9 A for DIQn.2
Controlling a digital input	Yes
Digital output functions, parameterizable	
<ul style="list-style-type: none"> • PTO (pulse train output) signal interface <ul style="list-style-type: none"> — 24 V asymmetrical — RS 422 symmetrical — TTL (5 V) asymmetrical • PTO (pulse train output) signal type <ul style="list-style-type: none"> — Pulse and direction — Count up, count down — Incremental encoder (A, B phase shift) — Incremental encoder (A, B phase shift, quadruple) 	Yes Yes Yes Yes Yes Yes Yes
Switching capacity of the outputs	
<ul style="list-style-type: none"> • with resistive load, max. 	0.1 A; 0.5 A for DIQn.2
Load resistance range	
<ul style="list-style-type: none"> • lower limit • upper limit 	240 Ω; 48 ohms for DIQn.2 12 kΩ
Output voltage	
<ul style="list-style-type: none"> • Type of output voltage • for signal "1", min. 	DC 23.2 V; L+ (-0.8 V), L+ (-1.3 V) for DIQn.2
Output current	
<ul style="list-style-type: none"> • for signal "1" rated value • for signal "1" permissible range, max. • for signal "1" minimum load current • for signal "0" residual current, max. 	0.1 A; 0.5 A for DIQn.2 0.12 A; 0.6 A for DIQn.2 2 mA 0.5 mA
Output delay with resistive load	
<ul style="list-style-type: none"> • "0" to "1", typ. • "1" to "0", typ. 	1 μs; 28 μs for DIQn.2 1 μs; 25 μs for DIQn.2
Switching frequency	
<ul style="list-style-type: none"> • with resistive load, max. • with inductive load, max. • For signal interface 24 V asymmetrical • For signal interface RS 422 symmetrical • For signal interface TTL (5 V) asymmetrical 	1 kHz; For DIQn.2 0.5 Hz; According to IEC 60947-5-1, DC-13, for DIQn.2 200 kHz; With DQn.0 and DQn.1 1 MHz 200 kHz
Cable length	
<ul style="list-style-type: none"> • shielded, max. 	600 m; 600 m for technological functions; depending on output frequency, load, and cable quality
Isochronous mode	
Bus cycle time (TDP), min.	250 μs; 375 μs if all 4 channels are used
Interrupts/diagnostics/status information	
Diagnostics function	Yes
Alarms	

• Diagnostic alarm	Yes	
Diagnoses		
• Monitoring the supply voltage	Yes	
• Short-circuit	Yes; Thermal overload protection	
• Group error	Yes	
Diagnostics indication LED		
• RUN LED	Yes; green LED	
• ERROR LED	Yes; red LED	
• MAINT LED	Yes; Yellow LED	
• Monitoring of the supply voltage (PWR-LED)	Yes; green LED	
• Channel status display	Yes; green LED	
• for channel diagnostics	Yes; red LED	
Potential separation		
Potential separation channels		
• between the channels	No	
• between the channels and backplane bus	Yes	
• Between the channels and load voltage L+	No	
Isolation		
Isolation tested with	707 V DC (type test)	
product functions / security / header		
signed firmware update	Yes	
Ambient conditions		
Ambient temperature during operation		
• horizontal installation, min.	-30 °C	
• horizontal installation, max.	60 °C; Observe derating	
• vertical installation, min.	-30 °C	
• vertical installation, max.	40 °C; Observe derating	
Altitude during operation relating to sea level		
• Installation altitude above sea level, max.	5 000 m; restrictions for installation altitudes > 2 000 m, see ET 200MP system manual	
Decentralized operation		
to SIMATIC S7-300	Yes; Via control and feedback interface	
to SIMATIC S7-400	Yes; Via control and feedback interface	
to SIMATIC S7-1200	Yes	
to SIMATIC S7-1500	Yes	
to standard PROFINET controller	Yes; Via control and feedback interface	
Dimensions		
Width	35 mm	
Height	147 mm	
Depth	129 mm	
Weights		
Weight, approx.	300 g	
Classifications		
	Version	Classification
eClass	14	27-24-22-05
eClass	12	27-24-22-05
eClass	9.1	27-24-22-05
eClass	9	27-24-22-05
eClass	8	27-24-22-05
eClass	7.1	27-24-22-05
eClass	6	27-24-22-05
ETIM	9	EC001422
ETIM	8	EC001422
ETIM	7	EC001422
Approvals / Certificates		
General Product Approval		

[KC](#)



[Manufacturer Declaration](#)

[Miscellaneous](#)



General Product Approval

EMV

For use in hazardous locations



[KC](#)



[CCC-Ex](#)

[EM](#)



For use in hazardous locations

Maritime application



[Type Examination Certificate](#)

[Miscellaneous](#)



Maritime application



[NK / Nippon Kaiji Kyokai](#)



last modified:

3/18/2025