



Figure similar

SIMATIC S7, digital output SM 322, isolated, 4 DO, 15 V / 20 mA 1 x 20-pole, for signals from the hazardous area, diagnostics-capable, PTB tested

Supply voltage	
Load voltage L+	
• Rated value (DC)	24 V
• Reverse polarity protection	Yes
Input current	
from load voltage L+ (without load), max.	160 mA
from backplane bus 5 V DC, max.	85 mA
Power loss	
Power loss, typ.	3 W
Digital outputs	
Number of digital outputs	4
Short-circuit protection	Yes; Electronic
• Response threshold, typ.	Output current with short-circuit protection, min. 20.5 mA + 10 %
Load resistance range	
• upper limit	200 Ω; Two-wire connection
Output voltage	
• Rated value (DC)	15 V
Output current	
• for signal "1" permissible range for 0 to 60 °C, max.	20 mA; ±10 %
Switching frequency	
• with resistive load, max.	100 Hz
Cable length	
• unshielded, max.	200 m
Interrupts/diagnostics/status information	
Diagnostics function	Yes
Diagnoses	
• Diagnostic information readable	Yes
• Short-circuit	Yes
Diagnostics indication LED	
• Group error SF (red)	Yes
• Status indicator digital output (green)	Yes
• Channel fault indicator F (red)	Yes
Ex(i) characteristics	
Module for Ex(i) protection	Yes
maximum values for connecting terminals for gas group IIC	
• U _o (no-load voltage), max.	15.75 V
• I _o (short-circuit current), max.	85 mA
• P _o (power output), max.	335 mW
• C _o (permissible external capacity), max.	500 nF

- Lo (permissible external inductivity), max.

5 mH

Potential separation

Potential separation digital outputs

- between the channels
- between the channels, in groups of
- between the channels and backplane bus
- Between the channels and load voltage L+

Yes; 60 V DC/30 V AC when used in the hazardous area; 400 V DC/250 V AC when used in NON-hazardous area

1

Yes; 60 V DC/30 V AC when used in the hazardous area; 400 V DC/250 V AC when used in NON-hazardous area

Yes; 60 V DC/30 V AC when used in the hazardous area; 400 V DC/250 V AC when used in NON-hazardous area

Standards, approvals, certificates

Use in hazardous areas

- ATEX marking
- FM marking
- Test number PTB

[EEx ib] IIC

AIS CL.1, DIV 1, GP A, B, C, D; CL.I, DIV 2, GP A, B, C, D T4

Ex-96.D.2102X

Ambient conditions

Ambient temperature during operation

- max.

60 °C

connection method

required front connector

20-pin

Dimensions

Width

40 mm

Height

125 mm

Depth

120 mm

Weights

Weight, approx.

230 g

Classifications

	Version	Classification
eClass	14	27-24-22-04
eClass	12	27-24-22-04
eClass	9.1	27-24-22-04
eClass	9	27-24-22-04
eClass	8	27-24-22-04
eClass	7.1	27-24-22-04
eClass	6	27-24-22-04
ETIM	9	EC001419
ETIM	8	EC001419
ETIM	7	EC001419
IDEA	4	3566
UNSPSC	15	32-15-17-05

Approvals / Certificates

General Product Approval

Test Certificates

other



[Miscellaneous](#)

[Miscellaneous](#)

[Confirmation](#)

Environment

[Environmental Con-
firmations](#)



[Environmental Con-
firmations](#)

last modified:

4/7/2025