



Figure similar

Complete unit combination 22 mm plastic black round pushbutton momentary with flat button with holder screw terminal, 1 NC red

product brand name	SIRIUS
product category	Commanding and signaling devices
product designation	Pushbutton
design of the product	Complete unit
product type designation	3SB6
product line	Plastic, black, 22 mm
number of command points	1
principle of operation of the actuating element	momentary
product extension optional light source	No
color of the actuating element	red
shape of the actuating element	round
product component front ring	No
material of the front ring	plastic
color of the front ring	black
product component light source	No
protection class IP	IP65
shock resistance according to IEC 60068-2-27	5g / 11 ms
vibration resistance according to IEC 60068-2-6	10 ... 500 Hz: 5g
mechanical service life (operating cycles) typical	3 000 000
electrical endurance (operating cycles) typical	3 000 000
Substance Prohibitance (Date)	03/01/2017
Weight	38 g
type of voltage	AC/DC
number of NC contacts for auxiliary contacts	1
number of NO contacts for auxiliary contacts	0
number of CO contacts for auxiliary contacts	0
ambient temperature	
• during operation	-25 ... +70 °C
• during storage	-40 ... +80 °C
mounting diameter	22 mm
mounting height	46.5 mm
installation width	30 mm

Approvals Certificates

General Product Approval

other

Environment



[Confirmation](#)

[Environmental Confirmations](#)

Further information

Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3SB6110-0AB20-1CA0>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3SB6110-0AB20-1CA0>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3SB6110-0AB20-1CA0>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3SB6110-0AB20-1CA0&lang=en



last modified:

12/21/2020 



Figure similar

Complete unit combination 22 mm plastic black round pushbutton momentary with flat button with holder screw terminal, 1 NO green

product brand name	SIRIUS
product category	Commanding and signaling devices
product designation	Pushbutton
design of the product	Complete unit
product type designation	3SB6
product line	Plastic, black, 22 mm
number of command points	1
principle of operation of the actuating element	momentary
product extension optional light source	No
color of the actuating element	green
shape of the actuating element	round
product component front ring	No
material of the front ring	plastic
color of the front ring	black
product component light source	No
protection class IP	IP65
shock resistance according to IEC 60068-2-27	5g / 11 ms
vibration resistance according to IEC 60068-2-6	10 ... 500 Hz: 5g
mechanical service life (operating cycles) typical	3 000 000
electrical endurance (operating cycles) typical	3 000 000
Substance Prohibitance (Date)	03/01/2017
Weight	38 g
type of voltage	AC/DC
number of NC contacts for auxiliary contacts	0
number of NO contacts for auxiliary contacts	1
number of CO contacts for auxiliary contacts	0
ambient temperature	
• during operation	-25 ... +70 °C
• during storage	-40 ... +80 °C
mounting diameter	22 mm
mounting height	46.5 mm
installation width	30 mm

Approvals Certificates

General Product Approval

other

Environment



EG-Konf.



CCC



[Confirmation](#)

[Environmental Confirmations](#)

Further information

Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3SB6110-0AB40-1BA0>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3SB6110-0AB40-1BA0>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3SB6110-0AB40-1BA0>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3SB6110-0AB40-1BA0&lang=en



last modified:

12/21/2020 



Complete unit combination 22 mm plastic black round illuminated pushbutton momentary with flat button with holder with integ. LED, 220V AC screw terminal, 1 NC red

product brand name	SIRIUS
product category	Commanding and signaling devices
product designation	Illuminated pushbutton
design of the product	Complete unit
product type designation	3SB6
product line	Plastic, black, 22 mm
number of command points	1
principle of operation of the actuating element	momentary
product extension optional light source	No
color of the actuating element	red
shape of the actuating element	round
product component front ring	No
material of the front ring	plastic
color of the front ring	black
product component light source	No
protection class IP	IP65
shock resistance according to IEC 60068-2-27	5g / 11 ms
vibration resistance according to IEC 60068-2-6	10 ... 500 Hz: 5g
mechanical service life (operating cycles) typical	3 000 000
electrical endurance (operating cycles) typical	3 000 000
Substance Prohibitance (Date)	03/01/2017
Weight	49 g
type of voltage	AC/DC
number of NC contacts for auxiliary contacts	1
number of NO contacts for auxiliary contacts	0
number of CO contacts for auxiliary contacts	0
ambient temperature	
• during operation	-25 ... +70 °C
• during storage	-40 ... +80 °C
mounting diameter	22 mm
mounting height	46.5 mm
installation width	30 mm

Approvals Certificates

General Product Approval

other

Environment



[Confirmation](#)

[Environmental Confirmations](#)

Further information

Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3SB6116-0DB20-1CA0>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3SB6116-0DB20-1CA0>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3SB6116-0DB20-1CA0>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3SB6116-0DB20-1CA0&lang=en



last modified:

12/21/2020 



Figure similar

Complete unit combination 22 mm plastic black round illuminated pushbutton momentary with flat button with holder with integ. LED, 220V AC screw terminal, 1 NO yellow

product brand name	SIRIUS
product category	Commanding and signaling devices
product designation	Illuminated pushbutton
design of the product	Complete unit
product type designation	3SB6
product line	Plastic, black, 22 mm
number of command points	1
principle of operation of the actuating element	momentary
product extension optional light source	No
color of the actuating element	yellow
shape of the actuating element	round
product component front ring	No
material of the front ring	plastic
color of the front ring	black
product component light source	No
protection class IP	IP65
shock resistance according to IEC 60068-2-27	5g / 11 ms
vibration resistance according to IEC 60068-2-6	10 ... 500 Hz: 5g
mechanical service life (operating cycles) typical	3 000 000
electrical endurance (operating cycles) typical	3 000 000
Substance Prohibitance (Date)	03/01/2017
Weight	49 g
type of voltage	AC/DC
number of NC contacts for auxiliary contacts	0
number of NO contacts for auxiliary contacts	1
number of CO contacts for auxiliary contacts	0
ambient temperature	
• during operation	-25 ... +70 °C
• during storage	-40 ... +80 °C
mounting diameter	22 mm
mounting height	46.5 mm
installation width	30 mm

Approvals Certificates

General Product Approval

other

Environment



[Confirmation](#)

[Environmental Confirmations](#)

Further information

Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3SB6116-0DB30-1BA0>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3SB6116-0DB30-1BA0>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3SB6116-0DB30-1BA0>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3SB6116-0DB30-1BA0&lang=en



last modified:

12/21/2020 



Complete unit combination 22 mm plastic black round illuminated pushbutton momentary with flat button with holder with integ. LED, 220V AC screw terminal, 1 NO green

product brand name	SIRIUS
product category	Commanding and signaling devices
product designation	Illuminated pushbutton
design of the product	Complete unit
product type designation	3SB6
product line	Plastic, black, 22 mm
number of command points	1
principle of operation of the actuating element	momentary
product extension optional light source	No
color of the actuating element	green
shape of the actuating element	round
product component front ring	No
material of the front ring	plastic
color of the front ring	black
product component light source	No
protection class IP	IP65
shock resistance according to IEC 60068-2-27	5g / 11 ms
vibration resistance according to IEC 60068-2-6	10 ... 500 Hz: 5g
mechanical service life (operating cycles) typical	3 000 000
electrical endurance (operating cycles) typical	3 000 000
Substance Prohibitance (Date)	03/01/2017
Weight	49 g
type of voltage	AC/DC
number of NC contacts for auxiliary contacts	0
number of NO contacts for auxiliary contacts	1
number of CO contacts for auxiliary contacts	0
ambient temperature	
• during operation	-25 ... +70 °C
• during storage	-40 ... +80 °C
mounting diameter	22 mm
mounting height	46.5 mm
installation width	30 mm

Approvals Certificates

General Product Approval

other

Environment



[Confirmation](#)

[Environmental Confirmations](#)

Further information

Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3SB6116-0DB40-1BA0>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3SB6116-0DB40-1BA0>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3SB6116-0DB40-1BA0>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3SB6116-0DB40-1BA0&lang=en



last modified:

12/21/2020 



Complete unit combination 22 mm plastic black round illuminated pushbutton momentary with flat button with holder with integ. LED, 220V AC screw terminal, 1 NO blue

product brand name	SIRIUS
product category	Commanding and signaling devices
product designation	Illuminated pushbutton
design of the product	Complete unit
product type designation	3SB6
product line	Plastic, black, 22 mm
number of command points	1
principle of operation of the actuating element	momentary
product extension optional light source	No
color of the actuating element	blue
shape of the actuating element	round
product component front ring	No
material of the front ring	plastic
color of the front ring	black
product component light source	No
protection class IP	IP65
shock resistance according to IEC 60068-2-27	5g / 11 ms
vibration resistance according to IEC 60068-2-6	10 ... 500 Hz: 5g
mechanical service life (operating cycles) typical	3 000 000
electrical endurance (operating cycles) typical	3 000 000
Substance Prohibition (Date)	03/01/2017
Weight	49 g
type of voltage	AC/DC
number of NC contacts for auxiliary contacts	0
number of NO contacts for auxiliary contacts	1
number of CO contacts for auxiliary contacts	0
ambient temperature	
• during operation	-25 ... +70 °C
• during storage	-40 ... +80 °C
mounting diameter	22 mm
mounting height	46.5 mm
installation width	30 mm

Approvals Certificates

General Product Approval

other

Environment



[Confirmation](#)

[Environmental Confirmations](#)

Further information

Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3SB6116-0DB50-1BA0>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3SB6116-0DB50-1BA0>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3SB6116-0DB50-1BA0>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3SB6116-0DB50-1BA0&lang=en



last modified:

2/5/2021 



Complete unit combination 22 mm plastic black round illuminated pushbutton momentary with flat button with holder with integ. LED, 220V AC screw terminal, 1 NO white

product brand name	SIRIUS
product category	Commanding and signaling devices
product designation	Illuminated pushbutton
design of the product	Complete unit
product type designation	3SB6
product line	Plastic, black, 22 mm
number of command points	1
principle of operation of the actuating element	momentary
product extension optional light source	No
color of the actuating element	white
shape of the actuating element	round
product component front ring	No
material of the front ring	plastic
color of the front ring	black
product component light source	No
protection class IP	IP65
shock resistance according to IEC 60068-2-27	5g / 11 ms
vibration resistance according to IEC 60068-2-6	10 ... 500 Hz: 5g
mechanical service life (operating cycles) typical	3 000 000
electrical endurance (operating cycles) typical	3 000 000
Substance Prohibition (Date)	03/01/2017
Weight	49 g
type of voltage	AC/DC
number of NC contacts for auxiliary contacts	0
number of NO contacts for auxiliary contacts	1
number of CO contacts for auxiliary contacts	0
ambient temperature	
• during operation	-25 ... +70 °C
• during storage	-40 ... +80 °C
mounting diameter	22 mm
mounting height	46.5 mm
installation width	30 mm

Approvals Certificates

General Product Approval

other

Environment



[Confirmation](#)

[Environmental Confirmations](#)

Further information

Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3SB6116-0DB60-1BA0>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3SB6116-0DB60-1BA0>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3SB6116-0DB60-1BA0>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3SB6116-0DB60-1BA0&lang=en



last modified:

2/5/2021 