




 PRODUCT-DETAILS

BEA16-4

BEA16-4 Connecting Link with Manual Motor Starter



General Information

Extended Product Type	BEA16-4
Product ID	1SBN081306T1000
EAN	3471523130739
Catalog Description	BEA16-4 Connecting Link with Manual Motor Starter
Long Description	BEA16-4 is an insulated connecting link used to connect AF09 ... AF16, AFC09 ... AFC16 or AFS09 ... AFS16 contactors with the MS116-0,16 ... MS116-25 or MS132-0,16 ... MS132-25 manual motor starters. The BEA16-4 ensures the electrical and mechanical connection between a contactor or reversing contactors and the associated manual motor starter.

Ordering

Minimum Order Quantity	10 piece
Customs Tariff Number	85389099

Popular Downloads

Data Sheet, Technical	1SBC100214C0202
-----------------------	-----------------

Information

Instructions and Manuals	1SBC101030M6801
Instructions and Manuals (Part 2)	1SAC200017M0002
CAD Dimensional Drawing	2CDC001079B0201

Dimensions

Product Net Width	45 mm
Product Net Depth / Length	63 mm
Product Net Height	41.8 mm
Product Net Weight	0.025 kg

Technical

Standards	UL 60947-4-1, CSA C22.2 No. 60947-4-1
Rated Operational Voltage	Main Circuit 690 V AC
Rated Frequency (f)	Main Circuit 50 / 60 Hz
Terminal Type	Screw Terminals
Suitable For	MO132 MS116 MS132 AF09 AF09Z AF12 AF12Z AF16 AF16Z AFC09 AFC12 AFC16 AFS09 AFS09Z AFS12 AFS12Z AFS16 AFS16Z MS132B AF09B AF09ZB AF12B AF12ZB AF16B AF16ZB

Product Name	Connecting Link
--------------	-----------------

Material Compliance

Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
REACH Declaration	2CMT2021-006202
RoHS Information	2CMT2021-006277
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
WEEE B2C / B2B	Business To Business
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Certificates and Declarations

Declaration of Conformity - CE	1SBD250021U1000
Declaration of Conformity - UKCA	1SBD250043U1000
GOST Certificate	GOST_POCCFR.ME77.B07175.pdf
RINA Certificate	RINA_ELE084013XG
UL Certificate	UL-US-L312527-151-12119002-5 UL-CA-L312527-451-12119002-5
UL Listing Card	UL_E312527

Container Information


Package Level 1 Units	box 10 piece
Package Level 1 Width	100 mm
Package Level 1 Depth / Length	187 mm
Package Level 1 Height	64 mm
Package Level 1 Gross Weight	0.25 kg
Package Level 1 EAN	3471523130739
Package Level 2 Units	box 10 piece
Package Level 2 Gross Weight	0.25 kg

External Classifications and Standards

ETIM 7	EC002498 - Accessories for low-voltage switch technology
ETIM 8	EC002498 - Accessories/spare parts for low-voltage switch technology
ETIM 9	EC002498 - Accessories/spare parts for low-voltage switch technology
eClass	V11.0 : 27371392
UNSPSC	39122221
IDEA Granular Category Code (IGCC)	5219 >> Switch part or accessory
E-Number (Finland)	3706556
E-Number (Sweden)	3211439

Categories

Low Voltage Products and Systems → Control Products → Contactors → Block Contactors






 PRODUCT-DETAILS

BEA26-4

BEA26-4 Connecting Link with Manual Motor Starter



General Information

Extended Product Type	BEA26-4
Product ID	1SBN082306T1000
EAN	3471523130746
Catalog Description	BEA26-4 Connecting Link with Manual Motor Starter
Long Description	BEA26-4 is an insulated connecting link used to connect AF26 ... AF38, AFC26 ... AFC38 or AFS26 ... AFS38 contactors with the MS116-0,16 ... MS116-16 or MS132-0,16 ... MS132-10 manual motor starters. The BEA26-4 ensures the electrical and mechanical connection between a contactor or reversing contactors and the associated manual motor starter.

Ordering

Minimum Order Quantity	10 piece
Customs Tariff Number	85389099

Popular Downloads

Data Sheet, Technical	1SBC100214C0202
-----------------------	-----------------

Information

Instructions and Manuals	1SBC101030M6801
Instructions and Manuals (Part 2)	1SAC200017M0002
CAD Dimensional Drawing	2CDC001079B0201

Dimensions

Product Net Width	45 mm
Product Net Depth / Length	48 mm
Product Net Height	41.8 mm
Product Net Weight	0.025 kg

Technical

Standards	UL 60947-4-1, CSA C22.2 No. 60947-4-1
Rated Operational Voltage	Main Circuit 690 V AC
Rated Frequency (f)	Main Circuit 50 / 60 Hz
Terminal Type	Screw Terminals
Suitable For	MO132 MS116 MS132 AF26 AF26Z AF30 AF30Z AF38 AF38Z AFC26 AFC30 AFC38 AFS26 AFS26Z AFS30 AFS30Z AFS38 AFS38Z MS132B AF26B AF26ZB AF30B AF30ZB AF38B AF38ZB

Product Name	Connecting Link
--------------	-----------------

Material Compliance

Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
REACH Declaration	2CMT2021-006202
RoHS Information	2CMT2021-006277
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
WEEE B2C / B2B	Business To Business
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Certificates and Declarations

Declaration of Conformity - CE	1SBD250021U1000
Declaration of Conformity - UKCA	1SBD250043U1000
GOST Certificate	GOST_POCCFR.ME77.B07175.pdf
RINA Certificate	RINA_ELE084013XG
UL Certificate	UL-US-L312527-151-12119002-5 UL-CA-L312527-451-12119002-5
UL Listing Card	UL_E312527

Container Information


Package Level 1 Units	box 10 piece
Package Level 1 Width	100 mm
Package Level 1 Depth / Length	187 mm
Package Level 1 Height	64 mm
Package Level 1 Gross Weight	0.25 kg
Package Level 1 EAN	3471523130746

External Classifications and Standards

ETIM 7	EC002498 - Accessories for low-voltage switch technology
ETIM 8	EC002498 - Accessories/spare parts for low-voltage switch technology
ETIM 9	EC002498 - Accessories/spare parts for low-voltage switch technology
eClass	V11.0 : 27371392
UNSPSC	39122221
IDEA Granular Category Code (IGCC)	5219 >> Switch part or accessory
E-Number (Finland)	3705822
E-Number (Sweden)	3211493

Categories

Low Voltage Products and Systems → Control Products → Contactors → Block Contactors






 PRODUCT-DETAILS

BEA38-4

BEA38-4 Connecting Link with Manual Motor Starter



General Information

Extended Product Type	BEA38-4
Product ID	1SBN082306T2000
EAN	3471523130753
Catalog Description	BEA38-4 Connecting Link with Manual Motor Starter
Long Description	BEA38-4 is an insulated connecting link used to connect AF26 ... AF38, AFC26 ... AFC38 or AFS26 ... AFS38 contactors with the MS116-20 ... MS116-32 or MS132-12 ... MS132-32 manual motor starters. The BEA38-4 ensures the electrical and mechanical connection between a contactor or reversing contactors and the associated manual motor starter.

Ordering

Minimum Order Quantity	10 piece
Customs Tariff Number	85389099

Popular Downloads

Data Sheet, Technical Information	1SBC100214C0202
-----------------------------------	-----------------

Instructions and Manuals	1SBC101030M6801
Instructions and Manuals (Part 2)	1SAC200017M0002
CAD Dimensional Drawing	2CDC001079B0201

Dimensions

Product Net Width	45 mm
Product Net Depth / Length	48 mm
Product Net Height	42.5 mm
Product Net Weight	0.03 kg

Technical

Standards	UL 60947-4-1, CSA C22.2 No. 60947-4-1
Rated Operational Voltage	Main Circuit 690 V AC
Rated Frequency (f)	Main Circuit 50 / 60 Hz
Terminal Type	Screw Terminals
Suitable For	MO132 MS116 MS132 AF26 AF26Z AF30 AF30Z AF38 AF38Z AFC26 AFC30 AFC38 AFS26 AFS26Z AFS30 AFS30Z AFS38 AFS38Z MS132B AF26B AF26ZB AF30B AF30ZB AF38B AF38ZB
Product Name	Connecting Link

Material Compliance

Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
REACH Declaration	2CMT2021-006202
RoHS Information	2CMT2021-006277
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
WEEE B2C / B2B	Business To Business
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Certificates and Declarations

Declaration of Conformity - CE	1SBD250021U1000
Declaration of Conformity - UKCA	1SBD250043U1000
GOST Certificate	GOST_POCCFR.ME77.B07175.pdf
RINA Certificate	RINA_ELE084013XG
UL Certificate	UL-US-L312527-151-12119002-5 UL-CA-L312527-451-12119002-5
UL Listing Card	UL_E312527

Container Information

Package Level 1 Units	box 10 piece
Package Level 1 Width	100 mm
Package Level 1 Depth / Length	187 mm
Package Level 1 Height	64 mm
Package Level 1 Gross Weight	0.3 kg
Package Level 1 EAN	3471523130753
Package Level 2 Units	box 10 piece
Package Level 2 Gross Weight	0.3 kg

External Classifications and Standards

ETIM 7	EC002498 - Accessories for low-voltage switch technology
ETIM 8	EC002498 - Accessories/spare parts for low-voltage switch technology
ETIM 9	EC002498 - Accessories/spare parts for low-voltage switch technology
eClass	V11.0 : 27371392
UNSPSC	39122221
IDEA Granular Category Code (IGCC)	5219 >> Switch part or accessory
E-Number (Finland)	3706557
E-Number (Sweden)	3211440

Categories

Low Voltage Products and Systems → Control Products → Contactors → Block Contactors

