










≥0.9	70Ra	IP66	50,000 Hours	AC100 240V	50-60Hz
Power Factor	CRI	Protection	Lifespan	Voltage	Frequency

## STREET LIGHT IP66

Model	 PSTT50L	 PSTT100L	 PSTT150L	 PSTT200L
LED chip	Nichia/Osram			
Wattage (W)	50W	100W	150W	200W
Efficacy (Lm/W)	130	130	130	130
Lumen (Lm)	6500	13000	19500	26000
Color temperature (K)	4500~5500			
Dimensions (mm) <small>(LxWxH)</small>	535x210x108	605x265x108	710x265x108	760x280x108
Operating temperature	-30~50°C			
Unit price (USD)				

## STREET LIGHT IP66

Model	 PSTP100L	 PSTP150L	 PSTP200L
LED chip	Nichia/Osram		
Wattage (W)	100W	150W	200W
Efficacy (Lm/W)	110	110	110
Lumen (Lm)	11000	16500	22000
Color temperature (K)	4500~5500		
Dimensions (mm) <small>(LxWxH)</small>	540x270x85	630x270x85	720x270x85
Operating temperature	-30~50°C		
Unit price (USD)	<b>\$197.17</b>	<b>\$246.30</b>	<b>\$286.26</b>

