




## OUTDOOR FLOODLIGHT POFA Series



$\geq 0.9$	80Ra	IP65	50,000 Hours	AC100 240V	50-60Hz
Power factor	CRI	Protection grade	Lifespan	Voltage	Frequency

### Outstanding features

- Nichia/Osram
- High quality aluminium alloy heat sink
- Energy saving
- No mercury, environmentally friendly
- Dustproof & Water-resistant
- Electrical safety assurance
- Easy installation and maintenance
- Perfect replacement for high pressure sodium and metal halide lamps

#### Note:

- Published lumen is total luminous flux of luminaire
- PF  $\geq 0.9$
- Lifespan: 50,000 hours
- CRI  $\geq 80$

## SPECIFICATION AND PRICE

Model	POFA100L	POFA150L	POFA200L	POFA250L
LED chip	Osram/Nichia			
Wattage (W)	100W	150W	200W	250W
Efficacy (Lm/W)	100	100	100	100
Lumen (Lm)	10000	15000	20000	25000
Color temperature (K)	4500~5500			
Dimensions (mm) (LxWxH)	267x292x110	267x380x110	267x469x110	267x588x110
Operating temperature	-30~50°C			
Unit price (USD)	<b>\$202.09</b>	<b>\$263.96</b>	<b>\$316.09</b>	<b>\$407.04</b>

#### Suggested installation areas

- Public areas
- Advertising board
- Sports complex
- Parking lot
- Landscape & facade
- Airport
- Parks & gardens